
HP Universal Adhesive Vinyl, 2 Pack





The HP DesignJet printing system—the complete solution

HP DesignJet and HP Scitex Printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



With Original HP 771 Vivid Photo Inks and Original HP 91 Photo Inks. Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhem Imaging Research, Inc. on a range of HP media. For more information, see **HPLFMedia.com**.

Quality prints for day-to-day production

Offer a range of indoor and outdoor displays

Produce quality color for your day-to-day production needs. Eye-catching displays—with a permanent, pressure-sensitive adhesive—are ideal for indoor applications.

See application and finishing versatility

Designed for a variety of applications and finishing techniques, HP Universal Adhesive Vinyl is a highly versatile media compatible with a variety of laminates to meet a wide range of application needs. See over 75 years indoor display permanence¹.

Enjoy quick post-print processing

Gain efficiency. ICC profiles help you get the color you need quickly. Fast dry time helps keep your workflow moving.

Target customers	Applications	Benefits	
Advertising agencies	Indoor	Outstanding image quality for day-to-day production	
Graphic artists	POP and retail displays	Fast dry time	
Sign shops	Banners	75+ years unlaminated indoor display permanence on HP Designjet Z-series printers ¹	
Print service providers		Designed for a range of applications and finishing methods	
		REACH compliant ⁹	
-			

Technical specifications



HP Universal Adhesive Vinyl, 2 Pack

For the latest ICC profiles/paper presets and a variety of resources to help you get the most out of your printer and HP large format materials, please visit **HPLFMedia.com**.

Weight (without liner)	150 g/m² per ISO 536 Test Method					
Weight (with liner)	290 g/m² per ISO 536 Test Method					
Thickness (without liner)	139 microns/5.5 mil per ISO 534 Test Method					
Thickness (with liner)	289 microns/11.4 mil per ISO 534 Test Method					
Opacity (with liner)	Greater than 96% per TAPPI T-425 Test Method and ISO 2471 Test Method					
Finish	Matte					
Operating temperature	15 to 35° C / 59 to 95° F					
Operating humidity	20 to 80% RH					
Display permanence (Indoor home or office)	75+ years, unlaminated with Original HP 771 Vivid Photo Inks and Original HP 91 Photo Inks ¹					
Water resistance	Moderately water resistant with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, and Original H 70 Photo Inks on the HP Designjet Z3200 Photo Printer series²					
Dry time	Less than 5 minutes (at 23° C, 50% RH)					
Lamination	Yes					
Shelf life	2 years, unopened in original packaging					
Storage temperature	15 to 35° C / 59 to 95° F					
Storage humidity	15 to 30% RH					
Country of origin	Product of China					
Ordering information	Product number	rs Roll sizes	UPC Codes	Region		
	C2T51A	914 mm x 20 m (36 in x 66 ft)	848412013627	North America, Europe		
	C2T52A	1067 mm x 20 m (42 in x 66 ft)	848412013634	North America, Europe		
Warranty	orkmanship. For warranty					

REACH

¹ Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhem Imaging Research, Inc. on a range of HP media. For more information, see **HPLFMedia.com/hp/t/printpermanence**.

- ² Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: HPLFMedia.com/hp/t/printpermanence.
- ³ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies. Logo source: Copyright European Chemicals Agency.

For detailed information on the HP large format printing materials portfolio and to order, see HPLFMedia.com

© 2016 Hewlett-Packard Development Company. © 2016 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of Hewlett-Packard Company and is used by Brand Management Group on license from Hewlett-Packard Company.

