

Dedicated Convenient Printer Suits Your Business Ecology

Long-lasting and worry-less printing with New Pantum P3305 series, dedicated to easing your work with automatic duplex printing, and long-running consumables. Designed to serve SMB and enterprise workgroups environment that needs large printing quantity, Pantum P3305 series is an eco-friendly and work-smart work companion.



MONO

Higher capacity cartridge and strong metal frame help you save money in a long run.



Wifi One Step Installation and Direct Printing



Automatic Duplex Printing



Low Cost and Saving Money



Convenient to Print



KEY SPECIFICATIONS



P3305 Series Monochrome Laser Printer

MODEL

■ P3305DN

■ P3305DW

PRINTING

Print technology	Mono laser	
Print speed	33ppm(A4)/35ppm(Letter)	
First print out time	Less than 8.2 seconds	
Maximum Monthly Duty Cycle	80000 pages	
Recommended Monthly Volume	1000 to 10000 pages	
Processor speed	350 MHz	
Memory	256 MB	
Resolution(dpi)	1200 x 600	
Printer language	PCL5e, PCL6, PS3, PDF	
Duplex mode	Auto	
Control panel	2Line LCD	
NFC	NO	Yes
Network print	Yes	
Wireless print	NO	Yes

PAPER HANDLING

Paper input tray	250 pages	
Multipurpose tray	1 pages	
Paper output tray	120 pages	
Media types	Plain, Thick, Transparency, Cardstock, Lable, Envelope	
Media sizes	A4, A5, JISB5, IS0 B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No. 10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2	
Media weight	Input tray: 60-105g/m ²	Multipurpose tray: 60-200g/m ²

GENERAL

Dimension (wxdxh)	354 x334x 232mm(13.9x 13.1x9.1in)	
Weight (without toner cartridge)	6.8kg (15lb)	
Operating temperature range	10-32 °C (50-95 °F)	
Operating humidity range	20% - 80% RH	
Input voltage	AC100-127V, 50/60Hz(±2Hz), 9A AC220-240V, 50/60Hz, 4.5A	
Noise	Printing: ≤52dB(A) Standby: ≤30dB(A)	
Power consumption	Print: Average 525W Standby: 50W Dormant: Less than 2 W	
Operating System compatibility	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10(32/64 bit); Mac OS 10.7~10.13; Linux: ubuntu12.04/14.04(32/64 bit);	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10(32/64 bit); Mac OS 10.7~10.13; Linux: ubuntu12.04/14.04(32/64 bit); iOS 7.0 and above; Android 4.4 and above
Interface	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx	High-speedUSB2.0 Ethernet: IEEE 802.3 10/100Base-Tx Wifi: IEEE 802.11b/g/n

SUPPLIES

Cartridge style	Separate drum and toner	
Starter cartridge capacity	TL-425H (3000 Pages)	
Starter drum unit lifetime ⁽²⁾ <small>(Print with A4 paper page by page discontinuously)</small>	DL-425X (25000 Pages)	
Cartridge and drum capacity ⁽¹⁾	Cartridge: TL-425H (3000 pages); TL- 425X (6000 pages); TL- 425U (11000 pages) Drum: DL-425X (25000 Pages)	

WHAT IN THE BOX

Printer × 1/ 3000 Page Toner Cartridge × 1/ 25000 Page Drum unit × 1/ USB Interface Cable × 1/
Power Cord × 1/ CD-ROM × 1/ Quick Setup Guide × 1

(1) Toner capacity is based on ISO 19752.

(2) Drum unit lifetime is based on 3 average letter/A4-size pages per print job and 5% coverage, actual lifetime affected by different printing habits and printing environment.