

PANTUM

The New Era for Printing

P3010 Series Monochrome Laser Printer

Offer eco-friendly and affordable prints whenever you need it

Start a worry-less printing with the new Pantum P3010 series today that has extremely low paper jam rate and highly budget-saving and more eco-friendly separate drum unit and toner cartridge. It is designed for users from SMB to large workgroup requiring easy-to-use and cost-effective office tools for their rapidly growing business.



Silent printing mode to lower the noise
and create a comfortable office environment



**Wifi One Step Installation
and Direct Printing**



**Office document direct
print from mobile devices**



**Low paper jam rate
design for engine**



High print speed



Convenient to print



Separate drum and toner



PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



P3010 Series Monochrome Laser Printer

Model	P3010D		P3010DW
Printing			
Print technology	Mono laser		
Print speed	30ppm(A4)/32ppm(Letter)		
First print out time	Less than 7.8 seconds		
Max. monthly volume	60000 pages		
Recommended monthly volume	750 to 3500 pages		
Processor speed	350 MHz		
Memory	128 MB		
Resolution(dpi)	1200x1200 dpi (Max)		
Printer language	GDI		
Duplex mode	Auto		
Control panel	LED		2Line LCD
NFC print	No		Yes
Network print	No		Yes
Wireless print	No		Yes
Paper handling			
Paper input tray	250 pages		
Multipurpose tray	1 pages		
Paper output tray	150 pages		
Media types	Plain,Thick,Transparency, Cardstock, Lable,Envelope		
Media sizes	A4, A5, JIS B5, Is0 B5 , A6, Letter, Legal,Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 Env, C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2		
Media weight	Input tray: 60-105g/m² Multipurpose tray: 60-200g/m²		
General			
Dimensions (wxdxh)	354 x334x 218mm(13.9x 13.1x8.6in)		354 x334x 232mm(13.9x 13.1x9.1in)
Weight (without toner cartridge)	6.8kg (15lb)		
Operating temperature range	10-32℃ (50-95°F)		
Operating humidity range	20% - 80% RH		
Input voltage	110V Model: AC100-127V(±10%), 50/60Hz(±2Hz), 9A 220V Model: AC220-240V(-15%,+10%), 50/60Hz(±2Hz), 4.5A		
Noise	Printing: ≦52dB(A) Standby: ≦30dB(A)		
Power consumption	Print:Average 525W Standby:50W Dormant:Less than 2 W		
Operating system compatibility	Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04);		Windows Server2003/2008/2012/ XP/ Vista/Win 7/Win 8/Win8.1/ Win10; Mac OS 10.7~10.13; Linux (ubuntu12.04/14.04); iOS 7.0 and above Android 4.4 and above
Interface	High-speedUSB2.0		High-speedUSB2.0 Ethernet:IEEE 802.3 10/100Base-Tx Wifi:IEEE 802.11b/g/n
Supplies			
Cartridge style	Separate drum and toner		
Starter cartridge capacity ⁽¹⁾	TL-410E (1000 pages)		
Cartridge and drum capacity ⁽¹⁾	Cartridge:TL-410 (1500 pages,Standard); TL-410H (3000 pages,High); TL- 410X (6000 pages ,Extra high) Drum:DL-410 (12000pages)		
Starter drum unit lifetime ⁽¹⁾ <small>(Print with A4 paper page by page discontinuously)</small>	DL-410E (9000 pages)		
What s in the box			
Pinter × 1/ 1000 Page Toner Cartridge × 1/ 9000 Page Drum unit × 1/ USB Interface Cable × 1/ Power Cord × 1/ CD-ROM × 1/ Quick Setup Guide × 1			

(1) Average yield per toner cartridge in accordance with ISO/IEC 19752 (Individual users will experience different results based on their environment and page coverage)

Copyright © 2017 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.